

### Product Overview

VCL-MX-XW, is an IEC 61850-3 compliant, sub-station hardened, industrial grade 52 Port Ethernet Switch, that is packaged in a 1U high, 19-inch rack-mountable shelf that can be installed in harsh operational environments. It requires no external fans or forced air cooling.

It offers a wide choice of 1+1 redundant power supply options which include 48V DC, 110-125V DC, 110V AC and 240V AC.

### Overview and Highlights

- **52 Ports, Sub-Station Hardened, Industrial Grade Switch**
  - **48 Gigabit Ethernet Ports:** 12 x 10BaseT/ 100BaseT/ 1000BaseT full-duplex Gigabit Ethernet ports.
  - **4 Gigabit Ethernet Optical Ports:** 4 x 1000BaseSX / LX Optical.

It is a fully managed switch that provides full compliance with IEEE 802.1p, IEEE 802.1Q, QoS, Differentiated Services (Diffserv) and packet priority classification protocols for traffic management and optimization.

The VCL-MX-XW is designed to operate in rugged environments even in extreme -20°C ~ 65°C (-4°F ~ 149°F) temperature conditions without any external fans or forced air cooling.

### Key Features

- Sub-Station Hardened Design
- IEEE 802.1
- Ethernet redundancy
- IEC 61850-3 and IEEE 1613 complied
- -20°C~65°C (-4°F ~ 149°F) operating temperature
- 1+1 redundant power supply

### Power Supply Options

- Dual Redundant (AC+ DC).
- 1+1 redundant AC power supply, 88~265V AC (50/60 Hz) Input
- 1+1 redundant DC power supply, 12~60V DC Input (-48V DC)
- 1+1 redundant DC power supply, 80~150V DC Input
- 1+1 redundant DC power supply, 125~373V DC Input
- EMI/EMC compliant.



### Ethernet Port Description:

- **52 Ports Sub-Station Hardened Switch**
  - **48 Gigabit Ethernet Ports:** 12 x 10BaseT/ 100BaseT/ 1000BaseT full-duplex Gigabit Ethernet ports.
  - **4 Gigabit Ethernet Optical Ports:** 4 x 1000BaseSX / LX Optical.
- All Copper Gigabit Ethernet Ports support auto-negotiation, auto-MDI/MDIX.
- All Optical Gigabit Ethernet Ports are full-duplex SFP based Gigabit Ethernet ports.
- Ethernet packet forwarding at wire-speed, non-blocking.
- User programmable bandwidth rate control on a per port basis (Ingress / Egress Rate Limiting).
- Flow Control.
- Reliable Store-and-Forward operation with data integrity checking.
- Supports up to 1632 Byte Frames.
- Supports VLAN and IEEE802.1Q VLAN tagging for Management Port.
- IEEE802.1p, 802.1Q and Differential Services (DS) QoS
- NTP Client. Updates time automatically from a user specified NTP server.

### Management Features

- USB console port.
- In-band Ethernet management. Telnet and SSH.
- Power LEDs.
- Real Time Clock (RTC).
- Automatic updating of RTC time. RTC shall update itself at user defined intervals from an NTP Server. The user shall define the IP address of the NTP server).
- Supports command line interface with predictive command completion.
- Supports IEEE802.1x security.
- Password Protected Access Control
- Access Logs
- Encrypted Password Protection
- SNMP V2/V3 Traps.

**Environmental:**

Operating Temperature	-4°F ~ 149°F (-20°C ~ 55°C)
Storage Temperature	-40°F ~ 185°F (-40°C ~ 85°C)
Operating Humidity	10%~95% relative humidity, non-condensing
Storage Humidity	10%~95% @40°C; non-condensing

**CE Compliance:**

- Low Voltage Directive 2014/35/EU
- Electromagnetic Compatibility 2014/30/EU

**EMI, EMC, Surge Withstand and other Compliances**

EN 50081-2	EN 50082-2	IEC 60068-2-29
IEC 61000-4-6 (Conducted Immunity)	IEC 60068-2-6	IEC 60068-2-2
IEC 60068-2-78	IEC 60068-2-1	IEC 60068-2-14
CISPR 32 / EN55032 Class A (Conducted Emission and Radiated Emission)		
IS 9000 (Part II Sec. 1-4, Part III Sec. 1-5, Part IV, Part 14 Sec. 1-3)		
IEC 60870-2-1	IEC 61000-4-5	
IEC 61000-4-3 (Radiated Immunity)	IEC 61000-4-8	
IEC 61000-4-2	IEC 61000-4-11	Telcordia
IEC 61000-4-4	GR-1089 Surge and Power Contact	

**Other Regulatory Compliances:**

- RoHS
- CE Marking
- Complies with FCC Part 68 and EMC FCC Part 15
- Telcordia GR-1089 Surge and Power Contact

**Ordering Information:**

Part #	Description
VCL-MX-XW-5024-xxxx*	VCL-MX-XW, Industrial Grade Ethernet Switch (IEC 61850-3 compliant) 19-inch 1U High Rack Mount version <b>52 Ports Sub-Station Hardened Switch:</b> – <b>48 Gigabit Ethernet Ports:</b> 12 x 10BaseT/ 100BaseT/ 1000BaseT full-duplex Gigabit Ethernet ports. – <b>4 Gigabit Ethernet Optical Ports:</b> 4 x 1000BaseSX / LX Optical. – Add *Power supply options (*xxxx power supply option)

**\* Power Supply Options:**

AC088~265R	2 x 88~265V AC Power Supply Input [1+1 Redundant Power Supply]
DC012~060R	2 x 12~60V DC Power Supply Input [1+1 Redundant Power Supply]
DC080~150R	2 x 80~150V DC Power Supply Input [1+1 Redundant Power Supply]
DC125~373R	2 x 125~373V DC Power Supply Input [1+1 Redundant Power Supply]

© Copyright: Valiant Communication

Technical specifications are subject to changes without notice.

Revision – 1.2, January 09, 2021

**U.K.**

Valiant Communications (UK) Ltd  
Central House Rear Office  
124 High Street, Hampton Hill  
Middlesex, TW12 1NS, U.K.

**E-mail:** gb@valiantcom.com

**U.S.A.**

Valcomm Technologies Inc.  
4000 Ponce de Leon Blvd.,  
Suite 470, Coral Gables,  
FL 33146, U.S.A.

**E-mail:** us@valiantcom.com

**INDIA**

Valiant Communications Limited  
71/1, Shivaji Marg,  
New Delhi - 110015,  
India

**E-mail:** mail@valiantcom.com